



## Valves

### Brass Ball Valves

Full Port 150# 600 WOG Teflon Seat Chrome Plated ball 2 Piece

#### GENERAL APPLICATIONS

Designed for control of air, water, oil, and gas in hose or pipe lines. Rated to 600 PSI WOG; 150 PSI Working Steam Pressure.

**Temperature Range Maximum 360F**

**Standard Size 1/4" Through 4"**

NUMBER	DESCRIPTION
07-2522	1/4"
07-2523	3/8"
07-2524	1/2"
07-2525	3/4"
07-2526	1"
07-2527	1 1/4"
07-2528	1 1/2"
07-2529	2"



Stainless Steel, UL Listed Ball Valves Available upon Request.

3" & 4" Available upon Request.

# BRASS LEVER VALVES

NUMBER	DESCRIPTION	
07-3532	3" BRASS LEVER DUMP VALVE	
07-3533	4" BRASS LEVER DUMP VALVE	
07-3534	6" BRASS LEVER DUMP VALVE	

# Polypropylene Ball Valves

Full Port Precision Molded Bolted Polypropylene Ball Valve

## GENERAL APPLICATIONS

Designed for easy flow. This valve is an economical alternative to brass valves. The Poly Ball Valves have excellent chemical resistance. They resist most acids, chemicals, and fertilizers.

## TEMPERATURE RANGE:

Maximum 180° F

## STANDARD SIZE

1" Through 4"

NUMBER	DESCRIPTION
07-3529	2" FNPT X FNPT
07-3531	3" FNPT X FNPT



NUMBER	DESCRIPTION
07-3539	2" FNPT X MALE CAM
07-3530	2" MNPT X MALE CAM



Other Sizes and Configurations Available Upon Request.